

## 3 Port 2b 1a PCI 1394b FireWire Adapter Card with DV Editing Kit

StarTech ID: PCI1394B\_3



The PCI1394B\_3 3-Port PCI FireWire Adapter Card turns a PCI slot into 2 FireWire 800 (IEEE 1394b) ports and 1 FireWire 400 (IEEE 1394a) port - a cost-effective solution that lets you connect FireWire 800 devices, as well as older FireWire 400 devices to your desktop computer.

A versatile FireWire solution, the adapter card works in both 5v and 3.3v PCI slots and in 64-bit and 32-bit operating environments, making it easy to create a high-speed laptop digital media center, or connect demanding FireWire peripheral devices such as portable hard drives, DV camcorders, digital cameras and CD-RW/DVD-RW drives.

This high quality adapter card is designed to provide reliable FireWire 800 and FireWire 400 connections, and is backed by StarTech.com's Lifetime Warranty.

### Applications and Solutions

- Add a high-speed FireWire port to a desktop without any FireWire ports
- Connect a digital camera to a PCI/PCI-X enabled desktop to download photos and video
- Connect a high-speed external hard drive to an PCI/PCI-X enabled system

## Features

- Two FireWire 800 ports with support for data transfer rates up to 800 Mbps
- One FireWire 400 port with support for transfer rates up to 400 Mbps
- Complaint with IEEE 1394-1995, 2000, 1394b and OHCI 1.1 standards
- Compliant with PCI revision 2.2 specifications
- Compatible with 3.3V/5V, 32/64-bit PCI or PCI-X slots
- Plug-and-Play and Hot-Swap compatible
- Includes Video Editing kit: Ulead Video Studio SE and FireWire cable

## Technical Specifications

- Warranty: Lifetime
- Interface: FireWire 400 (1394a)
- Bus Type: PCI / PCI-X (5 / 3.3V)
- Card Type: Standard Profile
- Chipset ID: Texas Instruments 3AA651W
- Product Height: 3.9 in [99 mm]
- Product Length: 6.57 in [167 mm]
- Maximum Data Transfer Rate: 800 Mbps
- Ports: 3
- OS Compatibility: Windows 98SE/ ME/ 2000/ XP(32/64bit)/ 2003(32/64bit)/ Vista(32/64bit)/ 7(32/64bit), Mac OS 10.2.4 and up, and Linux
- Carton Quantity: 50
- Industry Standards: PCI 2.2, OHCI, IEEE-1394B, IEEE-1394A, IEEE-1394
- Shipping (Package) Weight: 0.64 lb [0.29 kg]
- Product Weight: 3.14 oz [89 g]
- Product Width: 0.71 in [18 mm]
- System and Cable Requirements: Unused PCI slot

