

1 Port Native ExpressCard RS232 Serial Adapter Card with 16950 UART

Product ID: EC1S952



The EC1S952 1 Port Native ExpressCard RS232 Serial Adapter Card with 16950 UART lets you add an RS232 serial port to your laptop or ExpressCard-equipped desktop computer.

The serial ExpressCard is designed based on a single-chip architecture (as opposed to cards that use a "bridge chip"), providing native PCI Express communication for greater performance and reliability by reducing the CPU load by up to 48%, and lowering power consumption.

An included stabilizer bracket allows the EC1S952 to fit snugly in both 34mm and 54mm ExpressCard slots. Providing optimal communication with RS232 serial devices, this ExpressCard serial card supports baud rates of up to 115.2Kbps and features a 128-byte FIFO buffer, plus a high performance 16C950 UART.

Backed by a StarTech.com lifetime warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Self service automated machines and kiosks to control serial devices such as scales, touchscreens, magnetic card readers, bar code scanners, receipt printers, label printers
- POS retail applications in grocery stores, and any other retail store to control keyboards, cash drawers, receipt printers, card readers / card swipes, scales, and elevated displays on poles
- Used to control multiple surveillance / security cameras in a parking structure, office building, etc
- Standard ATM automated teller machines to control keypads, receipt printer, card readers / card swipes, touchscreen LCD's, camera control, etc
- Embedded system coding, building, and diagnostics

Features

- Supports high performance 16C950 UART with baud rates up to 115.2Kbps and backwards compatible with 16C550 UART
- ExpressCard 34mm and 54mm (with included adapter) Form Factor
- Single chip design optimizes speed, reliability and power
- Fully compliant with Express Card 1.0 Specifications
- Supports ASPM (L0S, L1) Link power management
- Automated in & out-of-band flow control
- Advanced FIFO fill management

Hardware	Warranty	Lifetime
	Bus Type	ExpressCard
	Card Type	34mm ExpressCard
	Chipset ID	PLX/Oxford - OXPICe952
	Interface	Serial
	Port Style	Integrated on Card
	Ports	1
Performance	FIFO	128 Bytes
	Max Baud Rate	115.2 Kbps
	Serial Protocol	RS-232
Connector(s)	Connector Type(s)	1 - ExpressCard (34mm)
	External Ports	1 - DB-9 (9 pin, D-Sub) Male
Software	OS Compatibility	Windows® CE 6.0 / 5.0, 95, 98SE, 2000, XP, XP Embedded, Vista, 7, 8, 8.1, 10 Windows Server® 2003, 2008 R2, 2012, 2012 R2, 2016 Linux 2.4.x to 4.4.x <i>LTS Versions only</i>
Environmental	Humidity	5~85% RH
	Operating Temperature	-10°C to 80°C (14°F to 176°F)
	Storage Temperature	-20°C to 100°C (-4°F to 212°F)
Physical Characteristics	Product Height	0.8 in [20 mm]
	Product Length	4.5 in [115 mm]
	Product Weight	1.2 oz [34 g]
	Product Width	1.8 in [45 mm]
Packaging Information	Shipping (Package) Weight	0.5 lb [0.2 kg]
What's in the Box	Included in Package	1 - ExpressCard to Serial Adapter 1 - 34 to 54mm slot spacer 1 - Driver CD 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.