

USB 3.0 to DisplayPort External Video Card Multi Monitor Adapter – 2560x1600

Product ID: USB32DPPRO



The USB32DPPRO USB 3.0 to DisplayPort® Multi Monitor Adapter functions as an external DisplayPort video card, turning an available USB 3.0 port into a DisplayPort output, with support for high resolution 2560x1600 video, and 5.1 surround sound audio. The USB 3.0 DisplayPort adapter delivers a convenient, high-performance external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your DisplayPort-capable display, and can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Certifications, Reports and Compatibility



Applications

- Add a secondary DisplayPort display and extend your desktop, without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to enhance multimedia presentations
- Great for researchers and writers, offering the ability to have reference material on one display while working on a separate document on another
- Increase productivity by running multiple applications on different screens - check your email on one display and search the web on the other
- View large or several spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using USB 3.0-capable laptop PCs, enabling connection to a secondary display/projector

Features

- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Supports resolutions up to 2560x1600
- DisplayLink 4K Plug-and-Display certified - automatic driver installation and updates
- USB-powered - No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the Windows® Aero interface
- Supports 5.1 channel audio
- Supports the use of multiple USB32DPPRO USB 3.0 DisplayPort adapters on a single system (up to 5)

Hardware	Warranty	2 Years
	Audio	Yes
	AV Input	USB 3.0
	AV Output	DisplayPort
	Chipset ID	DisplayLink - DL-3500
	Industry Standards	Standard DisplayPort, SuperSpeed USB 3.0, USB 2.0
	Memory	64MB, DDR2
	USB Pass-Through	No
Performance	Audio Specifications	5.1-Channel Surround (48Khz)
	General Specifications	This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.
	Maximum Digital Resolutions	2560x1600
	Note	If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.
	Supported Resolutions	Widescreen(16/32 bit): 2560x1600, 2560x1440, 2048x1152, 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720 Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB Type-A (9 pin) USB 3.0 Male
	Connector B	1 - DisplayPort (20 pin) Female
Software	OS Compatibility	Windows® 2000, XP, Vista, 7, 8, 8.1, 10 macOS 10.6 to 10.13.3, 10.14 Ubuntu 14.04, 16.04 Chrome OS v55+
Special Notes / Requirements	Note	Connect a maximum of five USB32DPPRO adapters on a single PC - See manual for system requirements Extended displays are currently only supported with DisplayLink-based products on macOS 10.11 to 10.13.3. This may change in future versions.

	System and Cable Requirements	Office Application: CPU: i3 Dual core 2.8GHz RAM: 2GB or higher Full HD Video: CPU: Quad Core 2.4GHz or Higher (i5 recommended) RAM: 4GB or higher Not intended for gaming
Power	Power Source	USB-Powered
Environmental	Humidity	20°C to 80°C (68°F to 176°F)
	Operating Temperature	0°C to 35°C (32°F to 95°F)
	Storage Temperature	-5°C to 40°C (23°F to 104°F)
Physical Characteristics	Color	Black
	Enclosure Type	Plastic
	Product Height	0.4 in [11 mm]
	Product Length	3.2 in [81 mm]
	Product Weight	0.6 oz [18 g]
	Product Width	1 in [26 mm]
Packaging Information	Shipping (Package) Weight	6.2 oz [177 g]
What's in the Box	Included in Package	1 - USB 3.0 to Displayport adapter
		1 - USB cable (39.25 inches)
		1 - driver CD
		1 - installation guide

Product appearance and specifications are subject to change without notice.