

## USB 3.0 to VGA External Video Card Multi Monitor Adapter for Mac and PC – 1920x1200 / 1080p

Product ID: USB32VGAPRO



The USB32VGAPRO USB 3.0 to VGA Adapter turns an available USB 3.0 port on your desktop or laptop into a VGA output, with high resolution 1920x1200/1080p video support - a convenient external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled Mac® or PC (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, and powered by the DisplayLink chipset, the USB32VGAPRO is our highest performing USB to VGA adapter, delivering high-resolution content to your VGA-capable display. The external graphics card can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

USB 3.0 port (backward compatible with USB 2.0)

## Certifications, Reports and Compatibility



## Applications

- Add a secondary VGA display and extend your desktop without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Use the adapter to connect your PC to your VGA-equipped TV, for showing family pictures and movies
- Great for researchers and writers, offering the ability to have reference material on one display and a working document copy on the other
- Increase productivity by running multiple applications on different screens, check your e-mail on one display and search the web on the other
- View a large spreadsheet or several individual spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using laptop PCs, enabling connection to a secondary display/projector

## Features

- SuperSpeed USB 3.0 (5 Gbps)
- Supports video resolutions up to 1920x1200/1080p
- USB-powered - No external power adapter required
- Supports Mirrored, Extended or Primary display configurations
- Supports display rotation

<b>Hardware</b>	Warranty	2 Years
	AV Input	USB 3.0
	AV Output	VGA
	Chipset ID	DisplayLink - DL-3100N
	Memory	512MB DDR2 SDRAM
	USB Pass-Through	No
<b>Performance</b>	General Specifications	This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.
	Maximum Analog Resolutions	1920x1200/1080p
	Note	If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.
	Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1366x768, 1280x800, 1280x768, 1280x720  Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1024x768, 800x600, 640x480
	Wide Screen Supported	Yes
<b>Connector(s)</b>	Connector A	1 - USB Type-A (9 pin) USB 3.0 Male Input
	Connector B	1 - VGA (15 pin, High Density D-Sub) Female Output
<b>Software</b>	OS Compatibility	Windows® 2000, XP, Vista, 7, 8, 8.1, 10 macOS 10.6 - 10.12, 10.14 Ubuntu 14.04, 16.04, 18.04 Chrome OS™ v55+
<b>Special Notes / Requirements</b>	System and Cable Requirements	Not intended for gaming
<b>Power</b>	Power Source	USB-Powered
<b>Environmental</b>	Humidity	<85% RH Non-Condensing
	Operating Temperature	10°C to 40°C (50°F to 104°F)
	Storage Temperature	-10°C to 80°C (14°F to 167°F)
<b>Physical Characteristics</b>	Cable Length	6.2 in [158.7 mm]
	Color	Black

	Enclosure Type	Plastic
	Product Height	0.8 in [20 mm]
	Product Length	10 in [255 mm]
	Product Weight	2.3 oz [64 g]
	Product Width	2.2 in [55 mm]
<b>Packaging Information</b>	Shipping (Package) Weight	5.6 oz [158 g]
<b>What's in the Box</b>	Included in Package	1 - USB 3.0 to VGA Video Adapter 1 - Driver/Software CD 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.